



# SAFEFlex Charger Datasheet

## Overview

The Lithium SAFEFlex Battery Charger is designed to operate with Material Handling (MH) and Ground Support Equipment (GSE) Lithium-ion batteries. This charger has universal AC power input, CANBus communications with the battery, has a touchscreen display, provides unity power factor with very low iTHD which results in very high charging efficiency, and has the smallest footprint in the MH and GSE charger industry.

This charger is offered in 15 KiloWatt (kW) and 30 kW models. Each model supports up to three simultaneous charging ports, and performs voltage auto-detect for each of the charging ports. This charger is scalable down to 5 kW and up to 30 kW, while each module has a default power level of 15 kW.

This charger supports local and remote management with an embedded Internet of Things (IoT) processor which provides real-time performance information of each charge session with a Lithium-ion battery. Local support and remote administrative staff can review and manage charger/truck integration and overall fleet performance. Access to the Internet is supported via an Ethernet port, WiFi communications, or GSM cellular communications via Sim card slot.

With this charger connected to our Maestro cloud-based applications, fleet managers can monitor all critical charging performance parameters such as voltage, temperature, charge/discharge current, charge time connected to the battery, Kilo-Watts delivered per charge session and warnings errors.

## Features

- Modular 15 kW and 30 kW models
- CANBus communications
- IoT Management via wireless and wired communications
- Real time performance monitoring via Maestro cloud-based application
- Easy configuration via touchscreen display
- Industry's highest energy density and efficiency, with smallest footprint.



## Performance Specifications


Parameter	Description	Value	
General	Battery Voltage Range (Auto Detect)	20 – 118 V	
	Maximum Output Charging Current	200 A per output (x3) or 600 A output (x1) on 30kW model	
	Power Loss in Standby Mode	< 10 W	
	Weight (lbs)	15 KW = 32 kg / 70.6 lb 30 KW = 42 kg / 92.6 lb	
	Dimensions (W x D x H)	23.622" x 11.811" x 13.77"	
	Input	AC Input Supply	380 – 480 Vac, 3-phase (3W+PE)
		Maximum AC Input current	50 Amps
Line Frequency		50 / 60 Hz	
Efficiency		> 97 %	
Power Quality		PF > 0.99; iTHD < 5%	
Connector and Wire		Phoenix Connector P/N: 1932504 6 AWG 4core	
Output		15 kW Model	100 – 300 A at 20 – 59 Vdc, or 50 – 150 A at 60 – 118 Vdc
	30 kW Model	200 – 600 A at 20 – 59 Vdc, or 100 – 300 A at 60 – 118 Vdc	
	Cable Length	Custom lengths	
	Connector Options	SB350, Euro A320 Connector	
	Connector and Wire	M6 Studs x 2 per line	
	Communication	Wireless	Wi-Fi, GSM (via SIM card slot)
		Wired	Ethernet, USB
Charge Control	Loading Method	User Control	
	Charging Profile	Default Factory Setting, User Configurable	
Environmental	Operating Temperature	-4°F to +122°F	
	Storage Temperature	-40°F to +176°F	
	Relative Humidity	Max. 85%	
	Ingress Protection Rating	IP21	
	Enclosure Ratings	NEMA 1	
Agency Approvals	United States	CEC UL 1564	
	Canada	CSA 22.2 107.2-01	
	Europe	IEC 62477-1	


### ABOUT GREEN CUBES TECHNOLOGY


Green Cubes Technology develops and manufactures a complete portfolio of lithium power systems that enable our OEM and enterprise customers to transition from Lead Acid and Internal Combustion Engine (ICE) power to Lithium-ion battery power. We utilize proven hardware and software platforms to build the most reliable lithium battery systems in our industries. With over 300 employees across five countries, Green Cubes has been producing reliable, high performance and high quality products for over 40 years.


Specifications subject to change without notice. Copyright 2025 © Green Cubes Technology



 [greencubes.com](https://greencubes.com)

 2121 East Boulevard Kokomo, IN 46902

 502-416-1060

 [info@greencubes.com](mailto:info@greencubes.com)